Revision Date: September 19, 2018 Revisions number: 6 supersedes 5

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: Type ACE™ Cleaner/Degreaser Wipe

Product ID numbers: ACE-1L

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Cleaner for Splice Preparation

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270 Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flammable: Flam Liq 2 H225 Eye Irritation: Eye Irrit. 2 H319 Drowsiness or dizziness: STOT SE 3 H336

2.2 Label elements

Contains: Acetone





Pictograms:

Signal word: Danger

Hazard Statements:

H225 Highly flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

Precautionary Statements:

P210 Keep away from sparks, flames and hot surfaces. No smoking.

P261 Avoid breathing vapor.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P305 + +P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

P338 if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical attention.

P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents according to local regulations.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

 Component
 CAS #
 EC #
 Wt. %

 Acetone
 67-64-1
 200-662-2
 >99.5

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes

with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with water. If irritation

occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Ingestion of small amounts of this material is not likely to be harmful. Ingestion of

large quantities may cause irritation of the digestive tract and/or nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). This is

an unlikely route of exposure in towelette package.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

Causes serious eye irritation.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

5.3 Advice for firefighters

Flammable. Wear self-contained breathing apparatus and protective clothing. Use water spray to keep fire-exposed containers cool. Vapors may cause a flash fire or ignite explosively.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package. For small spills: normal antistatic work clothes are usually adequate.

6.2 Environmental precautions:

Avoid release to the environment.

6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Acetone (67-64-1)

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min		
USA, OSHA NIOSH	2400 mg/m ³ , 1000 ppm			
USA, ACGIH	500 ppm	750 ppm		
British Columbia	250 ppm	500 ppm		
Alberta	1200 mg/m ³ , 500 ppm	1800 mg/m ³ , 750 ppm		
Quebec	1190 mg/m³, 500 ppm	2380 mg/m ³ , 1000 ppm		
Saskatchewan*	500 ppm	750 ppm		

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

^{*} Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.

9.1 Information of basic physical and chemical properties (bulk liquid)

Appearance: A non-linting towel, lightly saturated with acetone.

Odor threshold:

pH:

Does not apply

Freezing point:

-139°F / -95°C

Boiling point:

(initial) 133°F / 56°C

Flash point: (Initial) 133°F / 56°C (TCC)

Evaporation rate: 14.4 (n-butyl acetate = 1)

Flammability (solid, gas): Not applicable to liquids

Upper/lower flammability or
explosive limits: LEL: 2.6% (26°C)

UEL: 12.8% (66°C)

Vapor pressure: 30.8 kPa @25°C

Vapor density (Air = 1): 2.0 (Air = 1)

Specific gravity ($H_2O = 1$): 0.79 Solubility in water: Soluble

Coefficient of Water/Oil

Distribution:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 100%

VOC Content: Exempt (0 g/l)

10. Stability and Reactivity

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Acids, alkalis, reducing agents, strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

This product has low skin irritation potential. Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin

irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue.

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Acetone LD₅₀ (oral rat) 5800 mg/kg

LD₅₀ (dermal rabbit) >20000 mg/kg LC₅₀ (inhl rat) 16,000 ppm, 4hr

Chronic Exposure:

Reproductive Toxicity: Not classified as a reproductive system toxin.

Mutagenicity: Not classified as a mutagen.

Teratogenicity: Not classified as teratogenic or embryotoxic.

Specific Target Organ

Toxicity (STOT) No end point data.

Toxicologically Synergistic

Products: Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:

Ecotoxicity: No information available.

Aquatic Toxicity:

Fish (acute) 96 h LC₅₀ Rainbow Trout 4,740-6,330 mg/l

96 h LC₅₀ Bluegill 8,300 mg/l

96 h LC₅₀ Fathead Minnow 8,733 - 9,482 mg/l

12.2 Persistence and degradability:No information available12.3 Bioaccumulation potential:No information available12.4 Mobility in soil:No information available

12.5 Results of PBT and vPvBThis product is not, nor does it contain a substance that is a

Assessment: PBT or vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

US DOT Domestic Ground

Transportation: Not Regulated (See Special Provision 47).

UN Number: 3175

UN Proper shipping name: Solids Containing Flammable Liquid, N.O.S., (Contains: Acetone)

Transport hazard class(es): Class 4.1

Packing group:

Environmental hazards: None known **Special precautions:** None known

ICAO/IATA-DGR: Not Regulated (See Special Provision A46)
IMDG: Not Regulated (See Special Provision 216)

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

Components

All components are listed on the TSCA inventory.

Hazard Categories for SARA	<u>Acute</u>	Chronic	<u>Fire</u>	<u>Pressure</u>	Reactive
Section 311/312 Reporting	Yes	No	Yes	No	No

CERCLA/SARA Sec 302 SARA Sec. 313
Hazardous Substance RQ EHS TPQ Toxic Release

Acetone Yes (5000 lbs) No No

NFPA Ratings: Health: 1

Fire: 3 Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

California Proposition 65

WARNING: This product can expose you to benzene which is known to the state of California to cause cancer and birth defects and/or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

European Union

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

Australia

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD₅₀ = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)
DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

Mixture classification according to Regulation (EC) No 1272/2008: Classification Procedure

H225 Highly flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness
 Calculation method.
 Calculation method.

Revision Date: September 19, 2018

Revision Number: 7 NA

Supersedes: August 11, 2017 **Other:** Not Applicable

Indication of Changes: Section 3, 15 updated; format updates and additional California Proposition 65

information.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and

Canada HPR (SOR/2015-17)(WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.