SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: GrandSlam® **Type Q Subaqueous Pipe Joint Lubricant** (Winter Grade)

Product ID numbers: GWQ-35, GWQ-128, GWQ-448, GWQ-640

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Pipe joint lubrication.

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation 11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270 Email: sds@polywater.com

Polywater Europe BV Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen Netherlands Tel: +31 (0)10 2330578 Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

2. Hazards Identification

2.1 Classification of the substance or mixture Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).


Acute Tox 4 (oral)	H302
Acute Tox. 4 (Inhalation)	H332
STOT SE1	H370

2.2 Label elements

Contains:

Pictograms:

H302



- H332 Harmful if inhaled.
- H370 Causes damage to kidneys, heart, central nervous system, liver and eyes.

Precautionary Statements:

- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use outdoors or in a well-ventilated area.

Product Name: GrandSlam® Type Q Subaqueous Lubricant (Winter Grade) Revision Date: September 24, 2018

P301 + P312	IF SWALLOWED: Call for medical attention if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403 +P233	Store in a well-ventilated place. Keep cool.
2.3 Other hazards:	No information available.

3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Methanol	67-56-1	200-659-6	<10

This product contains no other reportable hazardous components under GHS Guidelines: OSHA 29 CFR 1910.1200, Canada HPR SOR/2015-17) and European Regulation (EC) No 1272/2008.

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact:	Flush eyes with a large quantity of water for 15 minutes. If irritation continues, seek medical attention.
Skin Contact:	If skin becomes irritated, wash area thoroughly with soap and water. If irritation continues, seek medical attention.
Inhalation (Breathing):	Remove to fresh air. Seek medical attention.
Ingestion (Swallowing):	If swallowed, get immediate medical attention. Induce vomiting unless told not to do so by medical personnel. Do not give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Aside from information above, no additional symptoms and effects are anticipated.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Water fog, foam, CO₂, dry chemical.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

High temperature steam; potentially carbon monoxide and carbon dioxide; paraffin wax fumes; formaldehyde.

5.3 Advice for firefighters

Sealed container can build up pressure when exposed to high heat. Cool containers with water.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Lubricant is extremely slippery. It should be washed, swept, or squeegeed from floor using wet mops.

6.2 Environmental precautions:

Outside, spills should be covered with sand, dirt, gravel or calcium chloride.

6.3 Methods materials for containment and cleaning up:

Oxidizing agents, such as household bleach, can be used to eliminate the slippery character.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid spills and clean them up immediately when they occur. Product is very slippery. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Keep product containers closed when not in use.

7.3 Specific end uses

See product flyer for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations: None

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Eye protection:

Safety glasses recommended.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

Appearance:	Opaque, cream to light-green gel.
Odor threshold:	Not Available
pH:	6.0 to 7.0
Freezing point:	18°F (-8°C)
Boiling point:	Not available
Flash point:	None to boiling (PMCC)
Evaporation rate:	Not available
Flammability (solid, gas): Upper/lower flammability or	Product is not flammable
explosive limits:	Does not apply
Vapor pressure:	Not available
Vapor density (Air = 1):	>1
Specific gravity (H ₂ O = 1):	0.97
Solubility in water:	Disperses
Partition coefficient: n- octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	>80,000 cps. @ 10 rpm.

9.2 Other Information

Product Name: GrandSlam® Type Q Subaqueous Lubricant (Winter Grade) Revision Date: September 24, 2018

Volatiles (Weight %):	\triangleright	80%
VOC Content:	97 g/l	

10. Stability and Reactivity

10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

None known.

10.5 Incompatible materials :

Avoid materials that react with water.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects: Acute toxicity

Eye contact:

Direct eye contact may cause eye irritation.

Skin contact:

Methanol may be absorbed through intact skin to produce systemic effect.

Irritation and Sensitization Potential:

This product may irritate skin. It is not a sensitizer.

Inhalation (Breathing):

Prolonged, repeated exposure or breathing high concentrations of methanol vapors may cause headache, nausea, vomiting, dizziness, visual disturbances, unconsciousness, and death. Toxic effects are exerted on the central nervous system, especially the optic nerve.

Ingestion:

Material contains less than 10% (by weight) methanol. Swallowing 100-250 ml of straight methanol can be fatal. Swallowing lesser quantities can cause blindness, dizziness, headaches, or nausea. Toxic effects are exerted on the central nervous system, especially the optic nerve.

Toxicity to Animals

Methanol:	LD ₅₀ (oral rat) 5628 mg/kg
	LD ₅₀ (dermal rabbit) 15800 mg/kg
	LC ₅₀ (inhl rat) 6400 ppm, 4hr

Aspiration hazard

Not an aspiration hazard.

Chronic Exposure:

Reproductive Toxicity:	Not Available
Mutagenicity:	Not Available
Teratogenicity:	Not Available
Toxicologically Synergistic	
Products:	Not Available
Carcinogenic Status:	This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

No information available.
Expected to be biodegradable.
No information available
No information available.
This product is not, nor does it contain a substance that is a PBT or vPvB.
None known.

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

UN Proper shipping name: Transport hazard class(es): Packing group: Environmental hazards: Special precautions: TDG:	Not Listed Not Applicable Not Applicable Not Applicable None known None known Not Regulated
TDG: ICAO/IATA-DGR: IMDG:	

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

Hazard Categories for SARA Section 311/312 Reporting		<u>Acute</u> Yes	Chronic No	<u>Fire</u> No	<u>Pressure</u> No	<u>Reactive</u> No
		CERC	LA/SARA Sec	302	SARA	Sec. 313
Components	Hazardo	us Subst	ance RQ	EHS TPQ	Toxic	Release
Methanol	Y	es (5,000	lbs.)	No	Yes	5 (1%)
NFPA Ratings:	Health:	1				
_	Fire:	0				
	Reactivity:	0				
NECTOR DUCES	A			1		

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

California Proposition 65

WARNING: This product can expose you to methanol which is known to the state of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

European Union

Product Name: GrandSlam® Type Q Subaqueous Lubricant (Winter Grade) Revision Date: September 24, 2018

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list \geq 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Canada

All components are listed on the DSL inventory. This product has been classified according to the hazard criteria of the CPR.

Australia

All components are listed on the AICS. Considered hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration CLP = Classification, Labeling and Packaging RegulationSTOT = Specific Target Organ Toxicity $<math>LD_{50} =$ Median Lethal Dose DNEL = Derived No Effect Level ACGIH = American Conference of Governmental Industrial Hygienists TSCA = Toxic Substances Control Act (USA) DSL = Domestic Substances List (Canada) AICS = Australian Inventory of Chemical Substances

Hazard Statements:	
--------------------	--

H302	Harmful if swallowed.
H332	Harmful if inhaled.
H370	Causes damage to kidneys, heart, central nervous system, liver and eyes.
Revision Date: Revision Number: Supersedes: Other: Indication of Changes:	September 24, 2018 7 July 31, 2017 Not Applicable Section 3, 15 updated; format updates and additional California Proposition 65 information. Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.