Revision Date: October 25, 2016 Revision Number: 6, supersedes 5

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name: Type HP™ Cleaner/Degreaser Saturated Towel/Wipe Package

Product ID numbers: HP-1, HP-P158ID, HP-D72, HP-D400UK, HP-P63

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Electrical cleaning
List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

Polywater Europe BV American Polywater Corporation Local Contact Info

Zuidhaven 9-11 Unit B2
4761 CR Zevenbergen
Netherlands
Tel: +31 (0)10 2330578

11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

National Poison Information Centre (NVIC): +31(0)30 274 8888 (Professional use for acute poisoning only, Netherlands.) Insert local poison control information here.

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to EU Regulation (EC) No 1272/2008 and Australia WHS Regulation (2011).

Skin Sens 1 H317 Aquatic Chronic 2 H411

2.2 Label elements

Contains: Petroleum distallates, hydrotreated light; d-Limonene





Pictograms:

Signal word: Warning

Hazard Statements:

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements:

P261 Avoid breathing fumes.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice.

P501 Dispose of contents/container in accordance with local and national regulations.

Notes: Aspiration classification not applied due to the physical form of the product.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

<u>Component</u>	CAS#	EC #	Wt. %	GHS/CLP Classification Asp. Tox. 1 H304;
Petroleum distillates,	0.47.40.47.0	005 440 0	400	EUH066
hydrotreated light	64742-47-8	265-149-8	< 100	Skin Irrit. 3 H316
				Flam Liq 3, H226
				Skin Irrit 2, H315
				Skin Sens 1, H317
				Aquatic Chronic 1, H410
d-Limonene	5989-27-5	227-813-5	< 10	Aquatic Acute 1, H400

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes

with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with water. If irritation

occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth. If victim is drowsy or

unconscious, place on the left side with head down. Do not leave victim

unattended. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

No information available.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates CO, CO2 and smoke. Smoke may be acrid and fumes irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Limited spill hazard with saturated towel package.

6.2 Environmental precautions:

Avoid release to the environment.

6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Petroleum	Distillates,	hydrotreated	light	(64742-47-8)	
		Long	40	avnacura limi	4

Country/Source	Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
Manufacturer, RCP* TWA Germany DFG**	1200 mg/m³ 350 mg/m³ (vapor); 5 mg/m³ (airborne particles)	 700 mg/m³ (vapor) 20 mg/m³ (airborne particles)
Australia	Not established	Not established
USA, ACGIH TWA USA, OSHA PEL	Not established 2000 mg/m ³ , 500 ppm (as petroleum distillates (naphtha))	Not established

D-Limonene (5989-27-5)

Long-term exposure limit – 8 hr TWA	Short-term exposure limit – 15 min
28 mg/m ³	112 mg/m ³
28 mg/m ³	110 mg/m ³
140 mg/m³	280 mg/m ³
110 mg/m³	220 mg/m³ (short term)
140 mg/m³	
Not established	Not established
Not established	Not established
Not established	Not established
	8 hr TWA 28 mg/m³ 28 mg/m³ 140 mg/m³ 110 mg/m³ Not established Not established

^{*}reciprocal calculation procedure for total hydrocarbons

^{**}Deutsche forschungsgemeinschaft, German Research Foundation

^{***}Norwegian regulations on Measures and Limit Values for Physical and Chemical Factors in the Work Environment and Infection Risk Group for Biological Agents

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. Towelette limits solvent vapor exposure. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use

0.4 mm

Nitrile, minimum 0.38 mm thickness or comparable protective barrier material with a high performance level for continuous contact use conditions, permeation breakthrough minimum 480 minutes in accordance with CEN standards EN 420 and EN 374.

Eye protection:

None necessary. Wipe package eliminates splash hazard. Do not allow wipe/towel to directly contact eyes.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties (bulk liquid)

Appearance: Clear, colorless liquid with a very light citrus scent.

Odor threshold: Not available pH: Does not apply

Freezing point: <-50°C

Boiling point: 185°C Initial

Flash point: >60,5°C Closed Cup (PMCC)
Evaporation rate: <0,1 (n-butyl acetate = 1)
Flammability (solid, gas): Not applicable to liquids

Upper/lower flammability or

explosive limits: LEL = 0.7% UEL = 6.1%-7.0%

Vapor pressure: < 134 Pa @ 20°C

Vapor density (Air = 1): > 1.0Specific gravity (H₂O = 1): 0.79Solubility in water: Nil

Partition coefficient: n-

octanol/water:Not availableAuto-ignition temperature:Not availableDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 100% VOC Content: 790 g/l

10. Stability and Reactivity

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials:

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It may cause an allergic skin reaction.

Inhalation (Breathing):

Concentrated petroleum solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Petroleum distillates,

hydrotreated light: LD₅₀ (oral rat) >5000 mg/kg

 LD_{50} (dermal rabbit) >2000 mg/kg LC_{50} (inhl rat) >4.3mg/L, 4 hours

d-Limonene: LD₅₀ (oral rat) >5000 mg/kg

LD₅₀ (dermal rabbit) 5000 mg/kg

RD₅₀ 1000 ppm

Aspiration hazard

Liquid solvent has an aspiration hazard. This route of exposure is not expected for towelette form.

Chronic Exposure:

Reproductive Toxicity: Not available.

Mutagenicity: Not available.

Teratogenicity: Not available.

Specific Target Organ

Toxicity (STOT) No end point data.

Toxicologically Synergistic

Products: Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:

Ecotoxicity: No information available. **Aquatic Toxicity:** No information available.

12.2 Persistence and degradability: Expected to be biodegradable.

12.3 Bioaccumulation potential:No information available **12.4 Mobility in soil:**No information available.

12.5 Results of PBT and vPvB This product is not, nor does it contain a substance that is a PBT or

Assessment: vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

UN Number: Not Listed **UN Proper shipping name:** Not Applicable Transport hazard class(es): Not Applicable Packing group: Not Applicable **Environmental hazards:** None known Special precautions: None known TDG: Not Regulated ICAO/IATA-DGR: Not Regulated IMDG: Not Regulated ADR/RID: Not Regulated

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

Australia

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia.

USA Federal and State

All components are listed on the TSCA inventory.

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD₅₀ = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

Mixture classification according to Regulation (EC) No 1272/2008: Classification Procedure

H317 May cause an allergic skin reaction.

Calculation method.
Calculation method.

H411 Toxic to aquatic life with long lasting effects.

Revision Date: October 25, 2016

Revision Number: 6 EU

Supersedes: January 2, 2015

Locale: -

Indication of Changes: Section 1, 2, 3, 8, 9, 15, 16 updated information and formatted for Europe.

Written in accordance with the provisions of REACH Annex II (EU No 453/2010) and

Australia WHS Regulation (2011). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.