

Polywater®

Type FD™



GENERAL ELECTRICAL AND CONTACT CLEANER



A Fast-Drying, Multipurpose Cleaner for Electrical and Industrial Use

Polywater® Type FD™ is excellent for cleaning busbar, splices, contacts, meters, communication radios, cable, and electrical apparatus. Polywater Type FD removes semiconductive residue, adhesive, silicone grease, grimes, tars, adhesives, lubrication fluids, fluxes, antioxidants, and contaminants without leaving residue.



FEATURES AND BENEFITS

- **FAST EVAPORATING**
Saves time and ensures moisture does not compromise electrical contacts or splices
- **MULTIPURPOSE**
One cleaning solvent for routine maintenance and electrical services
- **NO RESIDUE**
Evaporates completely, leaving no conductive residue
- **APPROVED**
Tested by medium and high voltage cable manufacturers
- **COMPATIBLE**
Does not corrode metal and is safe to use with most plastics

Polywater® Type FD™



CATALOG #	PACKAGE DESCRIPTION	UNITS/CASE
FD-9†	475 ml (16 oz) (475 ml) Aerosol Can	12
FD-35LF	1 qt (0.95 L) Bottle with Flip Top	12
FD-128††	1 gal (3.8 L) Jug	4
FD-640††	5 gal (18.9 L) Can	1
FD-DRUM††	55 gal (208 L) Drum	1

† Not available in Europe and Middle East.

†† Not available outside the USA and Canada.



SPECIFICATIONS AND APPLICATIONS

- **Compatibility:** FD Electrical Contact Cleaner will not corrode or stain metal parts. It does not tarnish or corrode copper per ASTM D130 and D1729.
- **Dielectric Strength:** 36kV per ASTM D877 standard test method.
- **Flash Point:** ~20°F (-5°C) per ASTM D56 standard test method.
- **Residue:** <100 ppm per ASTM D2369 standard test method.

polywater.com | +1 651-430-2270

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2022 American Polywater Corporation LIT-TYPEFDLYER/REV001

Polywater®
Solutions at work.

American Polywater Corporation
11222 60th Street N.
Stillwater, MN 55082 USA

+1 651-430-2270 Main
+31 10 233 0578 Europe, Middle East, N. Africa
email: support@polywater.com