

# SAFETY DATA SHEET – SET

## PowerPatch® Leak Repair Cartridge Kit

**Product ID numbers:** EPCT-KIT1, EPCT-KIT1G, EPCT-KITB6, EPCT-KIT06,  
EPCT-XXX (where XXX is the package/kit code.)  
EPCT-250KIT1, EPCT-250KIT, EPCT-250KITB6  
EPCT-250XXX (where XXX is the package/kit code.)

Date Compiled: March 8, 2022



### Supplier/Manufacturer:

#### American Polywater Corporation

11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

This product is a kit or a multi-part product with independent components. An SDS for each component is included. Do not separate SDSs.

### Contains

PowerPatch EPCT Cartridge Sealant Part A SDS  
PowerPatch EPCT Cartridge Sealant Part B SDS  
PowerPatch Putty Stick SDS  
Type RP Rapid Power Wipe SDS

SDSs are classified according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Each Kit may or may not contain all SDS components

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**PowerPatch® Cartridge Leak Repair Gel EPCT  
(Part A) SEALANT 84251**

**Product ID numbers:** EPCT-KIT1, EPCT-KIT1G, EPCT-KITB6, EPCT-KITB6G;  
EPCT-XXX (Where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Sealant/adhesive resin, Part A of 2-Part Sealant

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer:**

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 1-352-323-3500

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

**Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).**

Skin Irrit 2	H315
Skin Sens 1	H317
Eye Irrit 2A	H319

### 2.2 Label elements

**Contains:** Bisphenol A-epichlorohydrin polymer



**Pictograms:**

**Signal word:** Warning

**Hazard Statements:**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

**Precautionary Statements:**

P264	Wash hands thoroughly after handling.
P280	Wear protective gloves, protective clothing and eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

P333 + P313	If skin irritation or rash occurs: Get medical attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.
P362 + P364	Take off contaminated clothing.
P501	Dispose of container in accordance with local regulations

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Bisphenol A-epichlorohydrin polymer	25068-38-6	500-033-5	80 - 95

This product contains no other reportable hazardous components under OSHA 29 CFR 1910, 1200 Canada and European Regulation (EC) No 1272/2008. No additional ingredients require reporting based on applicable concentration and current supplier knowledge.

**4. First Aid Measures**

**4.1 Description of first aid measures**

**Eye Contact:** Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.

**Skin Contact:** Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.

**Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.

**Ingestion (Swallowing):** No emergency medical treatment necessary

**4.2 Most important symptoms and effects, both acute and delayed**

Refer to Section 11 for more information.

**4.3 Indication of immediate medical attention and special treatment needed.**

No information available.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Water fog or fine spray, dry chemical carbon dioxide, or foam.

**5.2 Special hazards arising from the substance or mixture**

Dense smoke is emitted when burned without sufficient oxygen.

**Hazardous decomposition and by-products:**

CO<sub>2</sub>, CO, phenolics. May contain other combustion products of varying composition which may be toxic or irritating.

**5.3 Advice for firefighters**

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate area. Use appropriate safety equipment.

**6.2 Environmental precautions:**

Avoid release to the environment. Prevent spill from entering drainage/sewer systems, waterways, basements or confined areas. Refer to Section 12 for more information.

**6.3 Methods materials for containment and cleaning up:**

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage****7.1 Precautions for safe handling**

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection****8.1 Control parameters****Exposure limits and recommendations:**

Contains no components with established Occupational Exposure Limit (OEL) values.

**8.2 Exposure controls****Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

**Protective gloves:**

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

**9. Physical and Chemical****9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	Dark gray or black gel.
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Does not apply
<b>Freezing point:</b>	Not available

<b>Boiling point:</b>	Not available
<b>Flash point:</b>	>400°F / >200°C (PMCC)
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not available
<b>Upper/lower flammability or explosive limits:</b>	Not available
<b>Vapor pressure:</b>	< 0.001 mm Hg @ 20°C
<b>Vapor density (Air = 1):</b>	>1
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	1.25 @ 25°C
<b>Solubility in water:</b>	Not available
<b>Partition coefficient: n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

**9.2 Other Information**

<b>Volatiles (Weight %):</b>	0%
<b>VOC Content:</b>	0 g/l

**10. Stability and Reactivity**

**10.1 Reactivity:**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

Hazardous reactions will not occur under normal transport or storage conditions.

**10.4 Conditions to avoid:**

Avoid high temperatures above 300 °C (572 °F). Decomposition can occur above 350 °C (662 °F). Generation of gas during decomposition can cause pressure to build in closed systems.

**10.5 Incompatible materials :**

Strong acids or bases (especially primary or secondary aliphatic amines), strong oxidizing agents.

**10.6 Hazardous decomposition products:**

CO<sub>2</sub>, CO, phenolics and other organic substances may be formed during combustion or elevated temperature degradation.

**11. Toxicological Information**

**11.1 Information on toxicological effects:**

**Acute toxicity**

**Eye contact:**

Direct eye contact with material or vapors may cause eye irritation.

**Skin contact:**

This product has moderate skin irritation potential. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Prolonged or repeated skin exposure may cause skin sensitization.

**Irritation and Sensitization Potential:**

May cause allergic skin reaction.

**Inhalation (Breathing):**

Low vapor pressure makes this route of exposure unlikely.

**Ingestion:**

Ingestion may cause irritation of the gastrointestinal tract.

**Toxicity to Animals:**

Bisphenol A Diglycidyl Ether: LD<sub>50</sub> (oral rat) >15,000 mg/kg  
 LD<sub>50</sub> (dermal rabbit) 23,000 mg/kg

**Aspiration Hazard:**

No aspiration hazard expected.

**Chronic Exposure:**

**Reproductive Toxicity:** Not available.  
**Mutagenicity:** Resins based on diglycidyl ether of bisphenol A have proved to be inactive when tested by in-vivo mutagenicity assays. These resins have shown activity in in-vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat-liver cells. The significance of these tests to humans is unknown.  
**Teratogenicity:** Not available.  
**Specific Target Organ Toxicity (STOT)** Not available.  
**Toxicologically Synergistic Products:** Not available.  
**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

**12. Ecological Information**

**12.1 Toxicity:**

**Aquatic Toxicity:** May be toxic to aquatic organisms.  
 Bisphenol A Diglycidyl Ether: LC<sub>50</sub> (96 hr.): 2 mg/l Oncorhynchus mykiss (rainbow trout) Semi-static test  
 Bisphenol A Diglycidyl Ether: EC<sub>50</sub> (48 hr.): 1.8 mg/l Daphnia magna (invertebrate) Static test  
 Bisphenol A Diglycidyl Ether: ErC<sub>50</sub> (72 hr.): 11 mg/l Fresh water algae (aquatic plants) Static test  
 Bisphenol A Diglycidyl Ether: Chronic Toxicity Value: Daphnia magna (invertebrate), 21 d, number of offspring, NOEC: 0.3 mg/l Semi-static test

**12.2 Persistence and degradability:**

Based on stringent OECD test guidelines, this material cannot be considered readily biodegradable. Biodegradability depends on environmental conditions.  
 Bisphenol A Diglycidyl Ether: OECD Biodegradation Test 302B 12% Biodegradation, 28 d exposure  
 Bisphenol A Diglycidyl Ether: Theoretical Oxygen Demand 2.35 mg/mg

**12.3 Bioaccumulation potential:**

Bioconcentration potential is moderate.

**12.4 Mobility in soil:**

Potential for mobility in soil is low..

**12.5 Results of PBT and vPvB Assessment:**

This product is not, nor does it contain a substance that is a PBT or vPvB.

**12.6 Other adverse effects:**

None known.

**13. Disposal Considerations**

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

<b>DOT:</b>	Not Regulated
<b>UN Number:</b>	3082
<b>UN Proper Shipping Name:</b>	Environmentally hazardous substance, liquid, N.O.S. (Bisphenol A)
<b>Class and Subsidiary Risk:</b>	9
<b>Packing Group:</b>	III
<b>ICAO/IATA-DGR:</b>	Not Regulated (See Special Provision A197)
<b>IMDG:</b>	Not Regulated (See IMDG Code 2.10.2.7)
<b>ADR/RID:</b>	9
<b>Other information</b>	For surface shipments within the United States: Not regulated.

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

<b>Hazard Categories for SARA Section 311/312 Reporting</b>	<u>Acute</u> Yes	<u>Chronic</u> No	<u>Fire</u> No	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------	----------------------	-------------------	-----------------------	-----------------------

<u>Components</u>	<b>CERCLA/SARA Sec 302</b> <u>Hazardous Substance RQ</u>	<b>SARA Sec. 313</b> <u>EHS TPQ</u> <u>Toxic Release</u>
The components of PowerPatch®-Leak Sealant Gel - Part A are not affected by these Superfund regulations.		

<b>NFPA Ratings:</b>	Health:	1
	Fire:	1
	Reactivity:	1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**California Proposition 65**

WARNING: This product can expose you to 2-(phenoxymethyl)-oxirane which is known to the state of California to cause cancer, and 4,4'-(1-methylethylidene)bis-phenol which is known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**Australia**

All components are listed on the AICS. Product is classified as hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

**16. Other Information**

**Abbreviations and acronyms:**

OSHA = Occupational Safety and Health Administration  
CLP = Classification, Labeling and Packaging Regulation  
STOT = Specific Target Organ Toxicity  
LD<sub>50</sub> = Median Lethal Dose  
DNEL = Derived No Effect Level  
ACGIH = American Conference of Governmental Industrial Hygienists  
TSCA = Toxic Substances Control Act (USA)  
DSL = Domestic Substances List (Canada)  
AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

**Classification Procedure**

- Calculation method.
- Calculation method.
- Calculation method.

**Revision Date:** March 4, 2022  
**Revision Number:** 11  
**Supersedes:** February 29, 2020  
**Other:** Not Applicable  
**Indication of Changes:** Section 8, 15 updated; added PPE pictograms, updated California Proposition 65 status.  
Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.



# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**PowerPatch® Cartridge Leak Repair Gel EPCT  
(Part B) SEALANT 84261**

**Product ID numbers:** EPCT-KIT1, EPCT-KIT1G, EPCT-KITB6, EPCT-KITB6G;  
EPCT-XXX (Where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Sealant/adhesive resin, Part B of 2-Part Sealant

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer:**

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 1-352-323-3500

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

**Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).**

Skin Irritation, Cat 2; H315

Eye Irritation, Cat 2; H319

Skin Sensitization, Cat 1; H317

### 2.2 Label elements

**Contains**

Polymer of C-18 Unsaturated Fatty Acid Dimers, 1,3-bis[3-(Dimethylamino)propyl] urea, Triethylenetetramine, Diethylene glycol bis (3-aminopropyl) ether



**Pictograms:**

**Signal word:**

Warning

**Hazard Statements:**

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

**Precautionary Statements:**

P264 Wash thoroughly after handling.  
P280 Wear protective gloves, protective clothing and eye protection.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 If skin irritation occurs: Get medical attention..

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists. Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local and national regulations.

**2.3 Other hazards:** No information available.

### 3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Polymer of C-18 Unsaturated Fatty Acid Dimers with TETA & TOFA	68082-29-1	500-191-5	10 - 15
1,3-bis[3-(Dimethylamino)propyl] urea	52338-87-1	257-861-2	3 - 7
Polymer of C-18 Unsaturated Fatty Acid Dimers	68541-13-9	--	3 - 7
Triethylenetetramine	112-24-3	203-950-6	1 - 3
Diethylene glycol bis (3-aminopropyl) ether	4246-51-9	224-207-2	1 - 3

This product contains no other reportable hazardous components under OSHA 29 CFR 1910, 1200 Canada and European Regulation (EC) No 1272/2008. No additional ingredients require reporting based on applicable concentration and current supplier knowledge.

### 4. First Aid Measures

#### 4.1 Description of first aid measures

<b>Eye Contact:</b>	Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
<b>Skin Contact:</b>	Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.
<b>Inhalation (Breathing):</b>	If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
<b>Ingestion (Swallowing):</b>	Wash out mouth with water. Do not induce vomiting. If victim is unconscious, place on the left side with head down. Never give anything by mouth to an unconscious person. Do not leave victim unattended. Seek medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

#### 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

### 5. Firefighting Measures

#### 5.1 Extinguishing media:

Water fog or fine spray, dry chemical carbon dioxide, or foam.

#### 5.2 Special hazards arising from the substance or mixture

Dense smoke is emitted when burned without sufficient oxygen.

#### Hazardous decomposition and by-products:

Oxides of carbon, oxides of sulfur, oxides of nitrogen. May contain other combustion products of varying composition which may be toxic or irritating.

#### 5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water

stream may spread fire.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate area. Use appropriate safety equipment.

### 6.2 Environmental precautions:

Avoid release to the environment. Refer to Section 12 for more information.

### 6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

### 7.2 Conditions for safe storage, including incompatibilities

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

### 7.3 Specific end uses

See technical data sheet on this product for further information.

## 8. Exposure Controls / Personal Protection

### 8.1 Control parameters

#### Exposure limits and recommendations:

Contains no components with established Occupational Exposure Limit (OEL) values.

### 8.2 Exposure controls

#### Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

#### Protective gloves:

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC.

#### Eye protection:

Safety glasses recommended.

#### Other protective equipment:

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.



**9. Physical and Chemical****9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	White to yellow gel; slight sulfur, pungent odor.
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Does not apply
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	Not available
<b>Flash point:</b>	>200°F / >90°C (PMCC)
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not available
<b>Upper/lower flammability or explosive limits:</b>	Not available
<b>Vapor pressure:</b>	<1 mm Hg @ 20°C
<b>Vapor density (Air = 1):</b>	Not available
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	1.2 @ 20°C
<b>Solubility in water:</b>	Not available
<b>Partition coefficient: n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

**9.2 Other Information**

<b>Volatiles (Weight %):</b>	0%
<b>VOC Content:</b>	0 g/l

**10. Stability and Reactivity****10.1 Reactivity:**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

Hazardous reactions will not occur under normal transport or storage conditions.

**10.4 Conditions to avoid:**

Avoid extreme heat and open flame.

**10.5 Incompatible materials :**

Strong oxidizing agents.

**10.6 Hazardous decomposition products:**

Oxides of carbon, oxides of sulfur, oxides of nitrogen and other organic substances may be formed during combustion or elevated temperature degradation.

**11. Toxicological Information****11.1 Information on toxicological effects:****Acute toxicity****Eye contact:**

Direct eye contact with material or vapors may cause eye irritation.

**Skin contact:**

May cause severe skin irritation, especially on prolonged contact. Prolonged or repeated skin exposure may cause skin sensitization.

**Irritation and Sensitization Potential:**

This product has high skin irritation potential. It is a sensitizer.

**Inhalation (Breathing):**

Low vapor pressure makes this route of exposure unlikely. No known significant hazard.

**Ingestion:**

Material is considered slightly toxic. Ingestion may cause irritation of the gastrointestinal tract, nausea, vomiting, and diarrhea.

**Toxicity to Animals:**

Polymercaptan amine blend	LD <sub>50</sub> (oral rat) >2,000 mg/kg
Polymer of C-18 Unsaturated Fatty Acid	
Dimers with TETA & TOFA	LD <sub>50</sub> (oral rat) >2,000 mg/kg
	LD <sub>50</sub> (dermal rabbit) >2,000 mg/kg
Triethylenetetramine	LD <sub>50</sub> (oral rat) 2,780 mg/kg
	LD <sub>50</sub> (dermal rabbit) 550 mg/kg

**Aspiration Hazard:**

No aspiration hazard expected.

**Chronic Exposure:**

<b>Reproductive Toxicity:</b>	Not available.
<b>Mutagenicity:</b>	Not available.
<b>Teratogenicity:</b>	Not available.
<b>Specific Target Organ Toxicity (STOT)</b>	Not available.
<b>Toxicologically Synergistic Products:</b>	Not available.
<b>Carcinogenic Status:</b>	This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

**12. Ecological Information**

**12.1 Toxicity:**

**Aquatic Toxicity:** Not available.

**12.2 Persistence and degradability:** Not available.

**12.3 Bioaccumulation potential:** Not available.

**12.4 Mobility in soil:** Not available.

**12.5 Results of PBT and vPvB Assessment:** This product is not, nor does it contain a substance that is a PBT or vPvB.

**12.6 Other adverse effects:** None known.

**13. Disposal Considerations**

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

**DOT:** Not Regulated

**UN Number:** Not Listed

**UN Proper Shipping Name:** Not Applicable

**Class and Subsidiary Risk:** Not Applicable  
**Packing Group:** Not Applicable  
**ICAO/IATA-DGR:** Not Regulated  
**IMDG:** Not Regulated  
**ADR/RID:** Not Regulated

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

<b>Hazard Categories for SARA Section 311/312 Reporting</b>	<u>Acute</u> Yes	<u>Chronic</u> No	<u>Fire</u> No	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------	----------------------	-------------------	-----------------------	-----------------------

<b>Components</b>	<b>CERCLA/SARA Sec 302 Hazardous Substance RQ</b>	<b>EHS TPQ</b>	<b>SARA Sec. 313 Toxic Release</b>
The components of PowerPatch®-Leak Sealant Gel - Part B are not affected by these Superfund regulations.			

**NFPA Ratings:**

Health:	2
Fire:	1
Reactivity:	1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**California Proposition 65**

WARNING: This product can expose you to chemicals including sulphuric acid, nitrilotriacetic acid, which is/are known to the State of California to cause cancer. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory.  
 This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**Australia**

All components are listed on the AICS.  
 Product is classified as hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

**16. Other Information**

**Abbreviations and acronyms:**

OSHA = Occupational Safety and Health Administration  
 CLP = Classification, Labeling and Packaging Regulation  
 STOT = Specific Target Organ Toxicity  
 LD<sub>50</sub> = Median Lethal Dose  
 DNEL = Derived No Effect Level

**Product Name:** PowerPatch® Cartridge Leak Repair Gel (Part B) Type EPCT

**Revision Date:** March 4, 2022

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.

**Classification Procedure**

- Calculation method.
- Calculation method.
- Calculation method.

**Revision Date:** March 4, 2022

**Revision Number:** 9 NA

**Supersedes:** September 20, 2018

**Other:** Not Applicable

**Indication of Changes:** Section 8, 15 updated; added PPE pictograms and revised California Proposition 65 information. Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format).

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name:**  
**PowerPatch® Putty Stick (EP-STICK)**  
**Part Numbers: 50822, 51043**

**Product ID numbers:** EP-STICK4;  
Contained in EP-KITXXX (Where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** 2-Part Putty Sealant for temporary repair

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

#### Supplier/Manufacturer:

**American Polywater Corporation**  
11222 - 60th Street North  
Stillwater, MN 55082 USA  
Tel: 1-651-430-2270  
Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

**Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).**

Skin Irrit 2	H315
Skin Sens 1	H317
Eye Irrit 2B	H319

### 2.2 Label elements

**Contains** Bisphenol A-epichlorohydrin polymer



#### Pictograms:

**Signal word:** Warning

#### Hazard Statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

#### Precautionary Statements:

P264	Wash hands thoroughly after handling.
P280	Wear protective gloves, protective clothing and eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.



P333 + P313	If skin irritation or rash occurs: Get medical attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.
P362 + P364	Take off contaminated clothing.
P501	Dispose of container in accordance with local regulations

**2.3 Other hazards:** No information available.

**3. Composition/Information on Ingredients**

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
Bisphenol A-epichlorohydrin polymer	25068-38-6	500-033-5	10 - 30

**4. First Aid Measures**

**4.1 Description of first aid measures**

- Eye Contact:** Immediately flush eyes with large quantity of water for 15 minutes. Seek medical attention.
- Skin Contact:** Remove contaminated clothing; flush skin thoroughly with soap and water for at least 15 minutes. If irritation or allergic reaction occurs, seek medical attention.
- Inhalation (Breathing):** If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention.
- Ingestion (Swallowing):** No emergency medical treatment necessary

**4.2 Most important symptoms and effects, both acute and delayed**

Refer to Section 11 for more information.

**4.3 Indication of immediate medical attention and special treatment needed.**

No information available.

**5. Firefighting Measures**

**5.1 Extinguishing media:**

Water fog or fine spray, dry chemical carbon dioxide, or foam.

**5.2 Special hazards arising from the substance or mixture**

Dense smoke is emitted when burned without sufficient oxygen.

**Hazardous decomposition and by-products:**

CO<sub>2</sub>, CO, phenolics. May contain other combustion products of varying composition which may be toxic or irritating.

**5.3 Advice for firefighters**

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Water fog may be used to cool fire exposed container to prevent pressure build-up and possible auto-ignition or rupture. Direct water stream may spread fire.

**6. Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate area. Use appropriate safety equipment.

**6.2 Environmental precautions:**

Avoid release to the environment. Prevent spill from entering drainage/sewer systems, waterways, basements or confined areas. Refer to Section 12 for more information.

**6.3 Methods materials for containment and cleaning up:**

Absorb spill with sand or absorbents. Residual resin may be removed using steam or hot soapy water. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Residual material can be removed with solvent.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage****7.1 Precautions for safe handling**

Avoid personal contact with the product. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Keep containers cool, dry, and away from sources of ignition. Keep containers and cartridges capped and sealed. Protect from freezing. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection****8.1 Control parameters****Exposure limits and recommendations:**

Contains no components with established Occupational Exposure Limit (OEL) values.  
A Derived No Effect Level (DNEL) of 12.25 mg/m<sup>3</sup> has been established for Acute Inhalation.

**8.2 Exposure controls****Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

**Protective gloves:**

The use of chemically resistant gloves is recommended to prevent skin contact. Suitable materials include nitrile (included in most kits), neoprene, ethyl vinyl alcohol (EVAL), PVC. Use a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374). NOTE: The selection of specific glove for the application should account for other chemicals in the environment, physical requirements and potential user reaction to the glove material.

**Eye protection:**

Safety glasses recommended.

**Other protective equipment:**

Use protective cream if skin contact is likely. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

**9. Physical and Chemical****9.1 Information of basic physical and chemical properties**

<b>Appearance:</b>	Gray/dark gray, solid putty stick. Pungent, sulfurous odor.
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Not available
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	Not available
<b>Flash point:</b>	>199.9°F / >93.3°C (PMCC)

<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not available
<b>Upper/lower flammability or explosive limits:</b>	Not available
<b>Vapor pressure:</b>	Not available
<b>Vapor density (Air = 1):</b>	Not available
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	2.247
<b>Solubility in water:</b>	Not available
<b>Partition coefficient: n-octanol/water:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	>392°F / >200°C
<b>Viscosity:</b>	Not available (thick putty)

## 9.2 Other Information

<b>Volatiles (Weight %):</b>	<0.1%
<b>VOC Content:</b>	0 g/l

## 10. Stability and Reactivity

### 10.1 Reactivity:

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability:

Stable

### 10.3 Possibility of hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4 Conditions to avoid:

Avoid high temperatures above 300 °C (572 °F). Decomposition can occur above 350 °C (662 °F). Generation of gas during decomposition can cause pressure to build in closed systems.

### 10.5 Incompatible materials :

Strong acids or bases (especially primary or secondary aliphatic amines), strong oxidizing agents.

### 10.6 Hazardous decomposition products:

CO<sub>2</sub>, CO, phenolics and other organic substances may be formed during combustion or elevated temperature degradation.

## 11. Toxicological Information

### 11.1 Information on toxicological effects:

#### Acute toxicity

##### Eye contact:

Direct eye contact with material or vapors may cause eye irritation.

##### Skin contact:

This product has moderate skin irritation potential. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material. Prolonged or repeated skin exposure may cause skin sensitization.

##### Irritation and Sensitization Potential:

May cause allergic skin reaction.

##### Inhalation (Breathing):

Low vapor pressure makes this route of exposure unlikely.

##### Ingestion:

Ingestion may cause irritation of the gastrointestinal tract.

**Toxicity to Animals:**

Bisphenol A Diglycidyl Ether: LD<sub>50</sub> (oral rat) >15,000 mg/kg  
 LD<sub>50</sub> (dermal rabbit) 23,000 mg/kg

**Aspiration Hazard:**

No aspiration hazard expected.

**Chronic Exposure:**

**Reproductive Toxicity:** Not available.  
**Mutagenicity:** Resins based on diglycidyl ether of bisphenol A have proved to be inactive when tested by in-vivo mutagenicity assays. These resins have shown activity in in-vitro microbial mutagenicity screening and have produced chromosomal aberrations in cultured rat-liver cells. The significance of these tests to humans is unknown.  
**Teratogenicity:** Not available.  
**Specific Target Organ Toxicity (STOT):** Not available.  
**Toxicologically Synergistic Products:** Not available.  
**Carcinogenic Status:** This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

**12. Ecological Information**

**12.1 Toxicity:**

**Aquatic Toxicity:** May be toxic to aquatic organisms.  
 Bisphenol A Diglycidyl Ether: LC<sub>50</sub> (96 hr.): 2 mg/l Oncorhynchus mykiss (rainbow trout)  
 Bisphenol A Diglycidyl Ether: Semi-static test  
 Bisphenol A Diglycidyl Ether: EC<sub>50</sub> (48 hr.): 1.8 mg/l Daphnia magna (invertebrate)  
 Bisphenol A Diglycidyl Ether: Static test  
 Bisphenol A Diglycidyl Ether: ErC<sub>50</sub> (72 hr.): 11 mg/l Fresh water algae (aquatic plants)  
 Bisphenol A Diglycidyl Ether: Static test  
 Bisphenol A Diglycidyl Ether: Chronic Toxicity Value: Daphnia magna (invertebrate), 21 d, number of offspring, NOEC: 0.3 mg/l  
 Bisphenol A Diglycidyl Ether: Semi-static test

**12.2 Persistence and degradability:**

Bisphenol A Diglycidyl Ether: Based on stringent OECD test guidelines, this material cannot be considered readily biodegradable. Biodegradability depends on environmental conditions.  
 Bisphenol A Diglycidyl Ether: OECD Biodegradation Test 302B  
 Bisphenol A Diglycidyl Ether: 12% Biodegradation, 28 d exposure  
 Bisphenol A Diglycidyl Ether: Theoretical Oxygen Demand  
 Bisphenol A Diglycidyl Ether: 2.35 mg/mg

**12.3 Bioaccumulation potential:**

Bioconcentration potential is moderate.

**12.4 Mobility in soil:**

Potential for mobility in soil is low..

**12.5 Results of PBT and vPvB Assessment:**

This product is not, nor does it contain a substance that is a PBT or vPvB.

**12.6 Other adverse effects:**

None known.

**13. Disposal Considerations**

Do not dump into sewer, on ground or into any body of water. Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

DOT: Not Regulated

<b>UN Number:</b>	3077
<b>UN Proper Shipping Name:</b>	Environmentally hazardous substance, solid, N.O.S. (Bisphenol A)
<b>Class and Subsidiary Risk:</b>	9
<b>Packing Group:</b>	III
<b>ICAO/IATA-DGR:</b>	Not Regulated (See Special Provision A197)
<b>IMDG:</b>	Not Regulated (See IMDG Code 2.10.2.7)
<b>ADR/RID:</b>	9
<b>Other information</b>	For surface shipments within the United States: Not regulated.

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

<b>Hazard Categories for SARA Section 311/312 Reporting</b>	<u>Acute</u> Yes	<u>Chronic</u> Yes	<u>Fire</u> No	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------	-----------------------	-------------------	-----------------------	-----------------------

<u>Components</u>	<u>CERCLA/SARA Sec 302 Hazardous Substance RQ</u>	<u>EHS TPQ</u>	<u>SARA Sec. 313 Toxic Release</u>
Components are not affected by these Superfund regulations.			

<b>NFPA Ratings:</b>	Health:	2
	Fire:	1
	Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**California Proposition 65**

WARNING: This product can expose you to 2-(phenoxyethyl)-oxirane which is known to the state of California to cause cancer, and 4,4'-(1-methylethylidene)bis-phenol which is known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list  $\geq 0.1\%$  SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory. This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**Australia**

All components are listed on the AICS. Product is classified as hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier.

**16. Other Information**

**Abbreviations and acronyms:**

OSHA = Occupational Safety and Health Administration

**Product Name:** PowerPatch® Putty Stick

**Revision Date:** March 4, 2022

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD<sub>50</sub> = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

**Mixture classification according to Regulation (EC) No 1272/2008:**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

**Classification Procedure**

Calculation method.

Calculation method.

Calculation method.

**Revision Date:** September 20, 2018

**Revision Number:** 8 NA

**Supersedes:** August 7, 2017

**Other:** Not Applicable

**Indication of Changes:** Section 8, 15 updated; added PPE pictograms and additional California Proposition 65 information. Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

### 1.1 Product identifier

**Product Name: Type RP™  
Rapid Power Electrical Cleaning Wipe**

**Product ID numbers:** RP-1, RP-1L  
RP-XXX (Where XXX is the package code.)

### 1.2 Relevant identified uses of the mixture and uses advised against

**Identified uses:** Utility Cleaner/Degreaser

**List of advices against:** Not applicable.

### 1.3 Details of the supplier of the safety data sheet

**Supplier/Manufacturer:**

**American Polywater Corporation**

11222 - 60th Street North

Stillwater, MN 55082 USA

Tel: 1-651-430-2270

Email: sds@polywater.com

### 1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification

### 2.1 Classification of the substance or mixture

**Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).**

Flam Liq 2 H225

Skin Irrit. 2 H315

STOT SE 3 H336

### 2.2 Label elements

**Contains:** 2-methylpentane, Low boiling point naphtha, 1-methoxypropan-2-ol



**Pictograms:**

**Signal word:** Danger

**Hazard Statements:**

H225 Extremely flammable liquid and vapor

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness

**Precautionary Statements:**

P210 Keep away from sparks, flames and hot surfaces. No smoking.

P261 Avoid breathing vapor.

P264 Wash hands thoroughly after handling.

P271	Use in a well-ventilated area.
P280	Wear protective gloves.
P303 + P361 + P353	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.
P332 + P313	If skin irritation occurs: get medical attention.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a doctor if you feel unwell.
P370 + P378	In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local and national regulations.

**Notes:** *Aspiration classification not applied due to the physical form of the product.*

**2.3 Other hazards:** No information available.

### 3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>
2-methylpentane	107-83-5	203-523-4	40 - 60%
Low boiling point naphtha	64742-89-8	265-192-2	40 - 60%
1-methoxypropan-2-ol	107-98-2	203-539-1	<10%

### 4. First Aid Measures

#### 4.1 Description of first aid measures

<b>Eye Contact:</b>	If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
<b>Skin Contact:</b>	Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
<b>Inhalation (Breathing):</b>	If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
<b>Ingestion (Swallowing):</b>	Do not induce vomiting or give anything by mouth unless directed to do so by medical personnel. Get medical attention if symptoms appear.

#### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

#### 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

### 5. Firefighting Measures

#### 5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

#### 5.2 Special hazards arising from the substance or mixture

##### Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

#### 5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

### 6. Accidental Release Measures



**6.1 Personal precautions, protective equipment and emergency procedures:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

**6.2 Environmental precautions:**

Avoid release to the environment.

**6.3 Methods materials for containment and cleaning up:**

Collect towel and absorb any excess material with sand or absorbents.

**6.4 Reference to other sections:**

Refer to Sections 4, 5, 8, and 13 for more information.

**7. Handling and Storage**

**7.1 Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

**7.2 Conditions for safe storage, including incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

**7.3 Specific end uses**

See technical data sheet on this product for further information.

**8. Exposure Controls / Personal Protection**

**8.1 Control parameters**

**Exposure limits and recommendations:**

**2-Methylpentane (107-83-5)**

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, ACGIH TWA*	500 ppm	1000 ppm
USA, OSHA PEL	500 ppm	1000 ppm
USA, NIOSH	100 ppm / 1800 mg/m <sup>3</sup>	--
Alberta, OEL	500 ppm / 1760 mg/m <sup>3</sup>	1000 ppm / 3500 mg/m <sup>3</sup>

**Low boiling point naphtha (64742-89-8)**

No information available

**1-Methoxypropane-2-ol (107-98-2)**

USA, ACGIH TWA*	50 ppm	100 ppm
Alberta, OEL	100 ppm / 369 mg/m <sup>3</sup>	150 ppm / 553 mg/m <sup>3</sup>
British Columbia, OEL	50 ppm	75 ppm
Ontario, OEL	50 ppm	100 ppm
Quebec, OEL	100 ppm / 369 mg/m <sup>3</sup>	150 ppm / 553 mg/m <sup>3</sup>
Saskatchewan, OEL	100 ppm	150 ppm

\* Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. British Columbia is based on current ACGIH TLV unless otherwise noted. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.

## 8.2 Exposure controls

### Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

### Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber  
For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use

Suggested Thickness: 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material.

Maximum wearing time should be determined based on 50 % of the penetration time determined by EN 374 part III.

### Eye protection:

Safety glasses recommended.

### Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.



## 9. Physical and Chemical

### 9.1 Information of basic physical and chemical properties

<b>Appearance:</b>	Clear, colorless liquid; mild odor.
<b>Odor threshold:</b>	Not available
<b>pH:</b>	Does not apply
<b>Freezing point:</b>	Not available
<b>Boiling point:</b>	144°F / 62°C (initial)
<b>Flash point:</b>	19°F / -7°C (TCC)
<b>Evaporation rate:</b>	>2 (n-butyl acetate = 1)
<b>Flammability (solid, gas):</b>	Not applicable to liquids
<b>Flammability limits:</b>	<b>LEL:</b> 1.2%
<b>Vapor pressure:</b>	Not available
<b>Vapor density (Air = 1):</b>	>1 (Air = 1)
<b>Specific gravity (H<sub>2</sub>O = 1):</b>	0.72
<b>Solubility in water:</b>	Not available
<b>Coefficient of Water/Oil Distribution:</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available

### 9.2 Other Information

<b>Volatiles (Weight %):</b>	100%
<b>VOC Content:</b>	720 g/l

## 10. Stability and Reactivity

**10.1 Reactivity:**

See remaining headings in Section 10.

**10.2 Chemical stability:**

Stable

**10.3 Possibility of hazardous reactions:**

None known.

**10.4 Conditions to avoid:**

Avoid heat, flame, and sparks.

**10.5 Incompatible materials :**

Strong oxidizing agents.

**10.6 Hazardous decomposition products:**

Carbon dioxide, carbon monoxide.

<b>11. Toxicological Information</b>
--------------------------------------

**11.1 Information on toxicological effects:****Acute toxicity****Eye contact:**

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

**Skin contact:**

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

**Irritation and Sensitization Potential:**

Product may be irritating to skin and eyes. It is not a sensitizer.

**Inhalation (Breathing):**

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**Ingestion:**

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

**Toxicity to Animals:**

2-methylpentane	No Data Available
Low boiling point naphtha	LD <sub>50</sub> (oral rat) >5,000 mg/kg LD <sub>50</sub> (dermal rabbit) >2,000 mg/kg Rabbit 4 hr. exposure: Irritating to skin, irritating to eyes
1-methoxypropan-2-ol	LD <sub>50</sub> (oral rat) 6,100 mg/kg LD <sub>50</sub> (dermal rabbit) 13,000 mg/kg LC <sub>50</sub> (inhl rat) >6 mg/l

**Chronic Exposure:**

**Reproductive Toxicity:** No data available.

**Mutagenicity:** No data available

**Teratogenicity:** No data available

**Specific Target Organ Toxicity (STOT)** No end point data.

**Toxicologically Synergistic Products:** Not available.

**Carcinogenic Status:**

**IARC** No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.

- OSHA** No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
- NTP** No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**12. Ecological Information**

- 12.1 Ecotoxicity:**
  - Aquatic Toxicity:** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
  - 2-methylpentane No Data Available
  - Low boiling point naphtha 96 h LC<sub>50</sub> Oncorhynchus mykiss (Rainbow Trout) 8.2 mg/l  
48 h EC<sub>50</sub> Daphnia magna (water flea) 4.5 mg/l  
96 h EC<sub>50</sub> Pseudokirchneriella subcapitata (green algae) 3.7 mg/l
  - 1-methoxypropan-2-ol 96 h LC<sub>50</sub> Pimephales promelas (Fathead Minnow) 20,800 mg/l  
48 h LC<sub>50</sub> Daphnia magna (water flea) 23,300 mg/l  
7 d EC<sub>50</sub> Pseudokirchneriella subcapitata (green algae) > 1000 mg/l
- 12.2 Persistence and degradability:** Expected to be biodegradable
  - Low boiling point naphtha 77% biodegradable, 28 d exposure time, method: OECD 301E
  - 1-methoxypropan-2-ol 96% biodegradable, 28 d exposure time, method: OECD 301E
- 12.3 Bioaccumulation potential:** No information available
- 12.4 Mobility in soil:** No information available
- 12.5 Results of PBT and vPvB Assessment:** This product is not, nor does it contain a substance that is a PBT or vPvB.
- 12.6 Other adverse effects:** None known.

**13. Disposal Considerations**

Dispose of product in accordance with National and Local Regulations.

**14. Transport Information**

- US DOT Domestic Ground Transportation:** Not Regulated (See Special Provision 47).
- UN Number:** 3175  
Solids Containing Flammable Liquid, N.O.S., (Contains: 2-methylpentane, Low boiling point naphtha)
- UN Proper shipping name:** Low boiling point naphtha
- Transport hazard class(es):** Class 4.1
- Packing group:** II
- Environmental hazards:** None known
- Special precautions:** None known
- ICAO/IATA-DGR:** Not Regulated (See Special Provision A46)
- IMDG:** Not Regulated (See Special Provision 216)

**15. Regulatory Information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**USA Federal and State**

All components are listed on the TSCA inventory.

**Hazard Categories for SARA**      Acute      Chronic      Fire      Pressure      Reactive

**Section 311/312 Reporting**                      Yes                      Yes                      Yes                      No                      No

	<b>CERCLA/SARA Sec 302</b>	<b>SARA Sec. 313</b>
<b><u>Components</u></b>	<b><u>Hazardous Substance RQ</u></b>	<b><u>EHS TPQ</u></b>
	<b><u>EHS TPQ</u></b>	<b><u>Toxic Release</u></b>
Components are not affected by these Superfund regulations.		

**NFPA Ratings:**

Health:	2
Fire:	3
Reactivity:	0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

**California Proposition 65**

WARNING: This product can expose you to benzene, ethylbenzene, and naphthalene which are known to the state of California to cause cancer, and toluene and benzene which are known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

**European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list  $\geq 0.1\%$  SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

**Canada**

All components are listed on the DSL inventory.  
This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**Australia**

All components are listed on the AICS.  
Hazardous according to criteria of NOHSC Australia.

**15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out for the mixture by the supplier

<b>16. Other Information</b>
------------------------------

**Abbreviations and acronyms:**

OSHA = Occupational Safety and Health Administration  
 CLP = Classification, Labeling and Packaging Regulation  
 STOT = Specific Target Organ Toxicity  
 LD<sub>50</sub> = Median Lethal Dose  
 DNEL = Derived No Effect Level  
 ACGIH = American Conference of Governmental Industrial Hygienists  
 TSCA = Toxic Substances Control Act (USA)  
 DSL = Domestic Substances List (Canada)  
 AICS = Australian Inventory of Chemical Substances

<b>Revision Date:</b>	March 4, 2022
<b>Revision Number:</b>	5 NA
<b>Supersedes:</b>	September 24, 2018
<b>Other:</b>	Not Applicable
<b>Indication of Changes:</b>	Section 8 updated; added PPE pictograms. Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

**Product Name:** Type RP™ Rapid Power Electrical Cleaner

**Revision Date:** March 4, 2022

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.