Revision Date: March 4, 2022 Revision Number: 7 supersedes 6

# **SAFETY DATA SHEET**

# 1. Identification of the substance/mixture and of the company

#### 1.1 Product identifier

Product Name: Type FD™ Electrical Contact Cleaner

Product ID numbers: FD-35LF, FD-128, FD-640, FD-DRUM

FD-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Electrical Cleaner/Degreaser

**List of advices against:** Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA Tel: 1-651-430-2270 Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

## 2. Hazards Identification

#### 2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Flam Liq 2 H225 Asp. Tox. 1 H304 Skin Irrit. 2 H315 STOT SE 3 H336 Rep. Tox. 2 H361

2.2 Label elements

**Contains:** Isohexanes, Ethanol, n-Pentane, n-Hexane, Isopropanol







Pictograms:

Signal word: Danger

**Hazard Statements:** 

H225 Extremely flammable liquid and vapor

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness

H361 Suspected of damaging fertility or the unborn child

**Precautionary Statements:** 

P210 Keep away from sparks, flames and hot surfaces. No smoking.

P242 Use only non-sparking tools.
P261 Avoid breathing vapor.

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves and eye protection.
P301 + P310 If swallowed: Immediately call a doctor.

P331 Do NOT induce vomiting.

P303 + P361 + If on skin: Take off immediately all contaminated clothing. Rinse skin with water.

P353

P308 + P313 If exposed or concerned: Get medical advice.

P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local and national regulations.

**2.3 Other hazards:** No information available.

## 3. Composition/Information on Ingredients

Component	<u>CAS #</u>	EC #	Wt. %
Isohexanes	107-83-5	203-523-4	80 -95%
Ethanol	64-17-5	200-578-6	<15%
n-Pentane	109-66-0	203-692-4	<3%
n-Hexane	110-54-3	203-777-6	<3%
Isopropanol	67-63-0	200-661-7	<2%

#### 4. First Aid Measures

## 4.1 Description of first aid measures

**Eye Contact:** If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes

with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

**Skin Contact:** Remove contaminated clothing; flush skin thoroughly with water. If irritation

occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth unless directed to do so by

medical personnel. Get medical attention if symptoms appear.

## 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

#### 4.3 Indication of immediate medical attention and special treatment needed.

Aspiration hazard. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis.

## 5. Firefighting Measures

## 5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

#### 5.2 Special hazards arising from the substance or mixture

## Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

## 5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

#### 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

#### 6.2 Environmental precautions:

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

## 6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

#### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

#### 7. Handling and Storage

## 7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

## 7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

#### 7.3 Specific end uses

See technical data sheet on this product for further information.

## 8. Exposure Controls / Personal Protection

## 8.1 Control parameters

Isohexane (107-83-5)

## **Exposure limits and recommendations:**

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, ACGIH	500 ppm	1000 ppm
USA, NIOSH TWA	100 ppm, 350 mg/m <sup>3</sup>	510 ppm, 1800 mg/m <sup>3</sup>
Alberta	1760 mg/m <sup>3</sup> , 500 ppm	3500 mg/m <sup>3</sup> , 1000 ppm
Quebec	1760 mg/m <sup>3</sup> , 500 ppm	3500 mg/m <sup>3</sup> , 1000 ppm
Saskatchewan*	500 ppm	1000 ppm

# Ethanol (64-17-5)

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, OSHA NIOSH	1900 mg/m <sup>3</sup> , 1000 ppm	
USA, ACGIH	1881 mg/m <sup>3</sup> , 1000 ppm	
Alberta	1880 mg/m <sup>3</sup> , 1000 ppm	
Ontario		1000 ppm
Quebec	1880 mg/m <sup>3</sup> , 1000 ppm	

Saskatchewan\* 1000 ppm 1250 ppm

n-Pentane (109-66-0)

11 1 01114110 (100 00 0)		
Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, OSHA NIOSH	1000 ppm	
British Columbia		
Alberta	600 ppm, 1700 mg/m <sup>3</sup>	
Ontario	600 ppm	
Quebec	120 ppm, 350 mg/m <sup>3</sup>	
Saskatchewan	600 ppm	750 ppm

n-Hexane (110-54-3)

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
USA, OSHA, NIOSH	180 mg/m³, 50 ppm	
USA, ACGIH	50 ppm	
British Columbia	200 ppm	400 ppm
Alberta	176 mg/m³, 50 ppm	
Ontario (skin)	50 ppm	
Quebec	176 mg/m <sup>3</sup> , 50 ppm	
Saskatchewan (skin)	50 ppm	62.5 ppm

## Isopropanol, 2-propanol (67-63-0)

	Long-term exposure limit –	Short-term exposure limit –
Country/Source	8 hr. TWA	15 min
USA, OSHA NIOSH	980 mg/m <sup>3</sup> , 400 ppm	1,225 mg/m <sup>3</sup> , 500 ppm
USA, ACGIH	200 ppm	400 ppm
British Columbia	200 ppm	400 ppm
Alberta	492 mg/m <sup>3</sup> , 200 ppm	984 mg/m <sup>3</sup> , 400 ppm
Ontario	200 ppm	400 ppm
Quebec	985 mg/m <sup>3</sup> , 400 ppm	1,230 mg/m <sup>3</sup> , 500 ppm
Saskatchewan*	200 ppm	400 ppm

<sup>\*</sup> Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavet and Northwest Territories are based heavily on current ACGIH TLVs.

## 8.2 Exposure controls

#### Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

#### **Protective gloves:**

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

#### Eye protection:

Safety glasses recommended.

#### Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.



## 9. Physical and Chemical

## 9.1 Information of basic physical and chemical properties

**Appearance:** Clear, colorless liquid; mild odor.

Odor threshold:

pH:

Does not apply

Freezing point:

Not available

Not available

144°F / 62°C

Flash point: >0°F / -18°C (TCC)

Evaporation rate: 1.7 (n-butyl acetate = 1)

Flammability (solid, gas): Not applicable to liquids

Flammability limits: LEL: 1.2% Vapor pressure: Not available Vapor density (Air = 1): >1 (Air = 1) Specific gravity (H<sub>2</sub>O = 1): 0.67

Solubility in water: Not available

Coefficient of Water/Oil

Distribution:Not availableAuto-ignition temperature:750.2°F / 399°CDecomposition temperature:Not availableViscosity:Not available

9.2 Other Information

Volatiles (Weight %): 100% VOC Content: 670 g/l

## 10. Stability and Reactivity

## 10.1 Reactivity:

See remaining headings in Section 10.

#### 10.2 Chemical stability:

Stable

#### 10.3 Possibility of hazardous reactions:

None known.

## 10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

## 10.5 Incompatible materials:

Strong oxidizing agents.

## 10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

## 11. Toxicological Information

## 11.1 Information on toxicological effects:

**Acute toxicity** 

Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

#### Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

#### Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

#### Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

## Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

## **Toxicity to Animals:**

Ethanol LD<sub>50</sub> (oral rat) 9000 mg/kg

Draize test, rabbit eye 500 mg/24 hours Mild

LC<sub>50</sub> (inhl rat) 20000, 10 hours

n-Pentane LC<sub>50</sub> (inhl rat) 364000 mg/m<sup>3</sup>, 4 hours

n-Hexane  $LD_{50}$  (oral rat) 25000 mg/kg

LC<sub>50</sub> (inhl rat) 48000, 4 hours

Isopropanol LD<sub>50</sub> (oral rat) 5000 mg/kg

 $LD_{50}$  (dermal rabbit) 12800 mg/kg  $LC_{50}$  (inhl rat) 12000, 8 hours

**Chronic Exposure:** 

Reproductive Toxicity: No data available.

Mutagenicity: No data available

Teratogenicity: No data available

**Specific Target Organ** 

Carcinogenic Status:

**Toxicity (STOT)** No end point data.

**Toxicologically Synergistic** 

**Products:** Not available.

This substance has not been identified as a carcinogen or probable

carcinogen by NTP, IARC, or OSHA, nor have any of its components. ACGIH classifies a component, n-hexane as Class A4, not classifiable for human or

animal and IARC classifies it as Class 3, not classifiable for human.

## 12. Ecological Information

12.1 Toxicity:

**Ecotoxicity:** No information available.

Toxic to aquatic organisms, may cause long-term adverse

**Aquatic Toxicity:** effects in the aquatic environment.

n-Hexane 96 h LC<sub>50</sub> Fathead Minnow (fish) 2.5 mg/l

48 h EC<sub>50</sub> Daphnia magna (water flea) 3,878 mg/l

3 h EC<sub>50</sub> Fresh water algae 12,840 mg/l

Isopropanol 96 h LC<sub>50</sub> Fathead Minnow (fish)> 1000  $\mu$ l/l

48 h LC<sub>50</sub> Golden Orfe 8970 - 9280 mg/l 96 h LC<sub>50</sub> Daphnid (crustacean)> 1000  $\mu$ l/l

**12.2 Persistence and degradability:**No information available **12.3 Bioaccumulation potential:**No information available

**12.4 Mobility in soil:**No information available

**12.5 Results of PBT and vPvB**This product is not, nor does it contain a substance that is a

**Assessment:** PBT or vPvB. **12.6 Other adverse effects:** None known.

#### 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

# 14. Transport Information

UN Number: 1993

**UN Proper shipping name:** Flammable Liquid N.O.S. (Contains: Isohexane, Ethanol)

Transport hazard class(es): 3
Packing group: ||

**Environmental hazards:** Marine Pollutant **Special precautions:** None known

ICAO/IATA-DGR: Flammable Liquid N.O.S. (Contains: Isohexane, Ethanol) 3; UN1993; PGII UN 1993, Flammable Liquid N.O.S. (Contains: Isohexane, Ethanol) 3; PGII

## 15. Regulatory Information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARA	<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	Reactive 1
Section 311/312 Reporting	Yes	No	Yes	No	No

CERCLA/SARA Sec 302 SARA Sec. 313
Components
n-Hexane

CERCLA/SARA Sec 302
Hazardous Substance RQ
Yes (5000 lbs.)
No

CERCLA/SARA Sec 302
EHS TPQ
No
Yes (1%)

NFPA Ratings: Health: 1
Fire: 3
Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

## **California Proposition 65**

WARNING: This product can expose you to chemicals including n-hexane which is known to the state of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

## **European Union**

Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Contains no substance on the REACH candidate list ≥ 0.1% SCL. Does not contain notified substances from the ELINCS List, Directive 92/32/EEC. Contains no REACH substances with Annex XVII restrictions.

#### Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

#### **Australia**

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia.

## 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier

## 16. Other Information

## Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD<sub>50</sub> = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

Revision Date: March 4, 2022

**Revision Number:** 7

**Supersedes:** September 24, 2018 **Other:** Not Applicable

**Indication of Changes:** Section 1, 8 updated; removed EU information, added PPE pictograms.

Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and

Canada HPR (SOR/2015-17) (WHMIS 2015). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.